

# LSH-9100-E

Load Securing Hooder





## UP TO 100 LOADS PER HOUR

#### Versatility

Configurable up to 6 different film types and sizes. Can do all pallet finishing. Cartesian stretch that allows many load sizes with one machine

#### Performance

Medium to fast capacity according to needs. Superior load protection.

#### **Cost efficiency**

Film usage reduced to a minimum and constant packaging cost. Cost efficient alternative to shrink wrapping.



Stretch hooding offers superior load protection by being waterproof, sand proof and dustproof, reducing damages on products and increasing load stability.

## **Applications**








Containers



Bottles



Bags

Trays




Big Bags

Barrels



## **Typical Equipment Dimensions**



Side view

Pallet dimensions 1200 mm X 1000 mm / 1219 mmx1016 mm

Loading height Min 300 mm, Max 2650 mm

Loading weight Up to 2000 kg

Palletized load dimensions Up to 1500 mm x 1300 mm

Load conveying height 600 mm above floor

Film thickness 40-200 microns

**Operating pressure** 85 PSI (6 bar)

Electrical requirements & net frequency 50-60 Hz

Ambient temperature +0°C +40°C

Noise level  $\leq 80 \text{ dB}$ 

## Features

Film unwinding with double motor, film opening with vacuum system

Photocells film end, on all reels

Four supporting columns for vertical stretch on all load sizes

Automatic load identification system, and tailored hood for ECAH load

Multiple reels configuration

Controllable and adjustable sealing bar temperature

Film usage reduced to a minimum

#### Options

Centering device for pallets

Second reel in automatic cycle

Maintenance for welding and cutting bar at floor level

Outfeed at 90°

EWON for remote assistance

Increase HMI size

Upgrade to stairs



## **Client Solutions**

**Premier Tech Client Solutions** take a personalized approach to **lifecycle management**, creating enhanced solutions customized to your specific needs that develop your own capabilities and operational habits, and help you achieve and maintain productivity.

The Client Solutions' passionate team acts as a **partner** by maintaining constant collaboration and putting your interests at the heart of daily decisions throughout your equipment's lifecycle.

Our programs are designed to help you reach your highest **Overall Equipment Effectiveness (OEE)** and maximize your **Return on Investment (ROI)** by providing you with the most valuable lifecycle services in the industry focusing on critical areas such as **24/7 technical support, spare parts, field service, training, system assessments and optimization.** 



The information contained in this brochure is based upon the latest information available at the time of publication and is designed to provide you with a general introduction to our products. We make no warranties or representations as to its accuracy. We are continually updating and improving our products and reserve the right to amend, discontinue or alter specifications and prices without prior notice. Premier Tech is a registered trademark of Premier Tech Ltd © Premier Tech Ltd. 2019